

DREXELBROOK®

The Point™ Two-Wire RF Series Point Level Switch



One of the Drexelbrook RF Point Level Switches You Won't Have to Calibrate

Simply install ThePoint Series into the tank and apply power...that's it! Unlike other RF or capacitance systems that require calibration via setpoint potentiometers, jumpers, magnets, or pushbuttons, ThePoint Series reliably detects the absence or presence of material without any adjustments.

ThePoint Series software continuously monitors the application for changes in composition, dielectric or conductivity, and maintains a repeatable trip point on the probe. Other RF and capacitance systems require calibration adjustments when the process material is changed. Since ThePoint Series recognizes changes in material, it is ideal for non-dedicated tanks that are used for a wide variety of products.

Intelligent Electronics Save Time and Money

- UNIQUE! - NO calibration or setpoint adjustments.
- UNIQUE! - Ignores changes in dielectric or conductivity.
- Automatically recognizes and ignores coatings to prevent false alarms.

Diverse Applications

- Detects the absence or presence of liquids, slurries, and granulars.
- Capable of high pressures and temperatures.

Economical Without Sacrifice

- Retains superior performance.
- Less maintenance than other technologies; no moving parts to hang up or wear out.

Output

- 8mA (Alarm), 16mA (Normal)
or
- 8mA (Normal), 16mA (Alarm)

Lower Cost of Ownership

In addition to lower initial investment, ThePoint continues to save with little or no maintenance compared with other technologies. Further, the sensor can be lengthened or shortened in the field, saving need for additional purchases.

Remote or Integral Electronics

Unlike many technologies, electronics can be remote mounted to a convenient or safe location.

The Point™

Specifications

Technology:

RF Admittance

Calibration:

None

Modes Of Operation:

High and Low Level

Repeatability:

2 mm (0.08 inch) conductive liquids

Response Time:

Less than one second

Ambient Electronic Temperature:

-40 to 70°C (-40 to 158°F)

Storage Temperature:

-40 to 85°C (-40 to 185°F)

Indicators:

LEDs: Green Power, Red Alarm

Time Delay:

0-60 seconds, forward or reverse-acting

Supply Voltage:

13-30 VDC

Power Consumption:

2 watts maximum

Output:

8mA (Alarm), 16mA (Normal)

or

8mA (Normal), 16mA (Alarm)

Housing:

Powder-Coated aluminum with two cable entries.

Cable Entry:

M20 x 1.5 or ¾-inch NPT

Ingress Protection:

IP66 NEMA 4X

Approvals:

Integral



Explosion Proof for Class I, Division 1, Groups B, C, and D; Dust Ignition Proof for Class II, III, Division 1, Groups E, F, and G; Non Incendiary for Class I, Division 2, Groups A, B, C, and D; Suitable for Class II, III, Division 2, Groups F and G hazardous (classified) locations Outdoor Type 4, 4X, IP66 with Intrinsically Safe connections to Class I, II, III, Division 1, Groups A, B, C, D, E, F, and G hazardous (classified) locations in accordance with control drawing 420-0004-220-CD

Remote

Explosion Proof for Class I, Division 1, Groups A, B, C, and D; Dust Ignition Proof for Class II, III, Division 1, Groups E, F, and G; Non Incendiary for Class I, Division 2, Groups A, B, C, and D; Suitable for Class II, III, Division 2, Groups F and G hazardous (classified) locations Outdoor Type 4, 4X, IP66 with Intrinsically Safe connections to Class I, II, III, Division 1, Groups A, B, C, D, E, F, and G hazardous (classified) locations in accordance with control drawing 420-0004-220-CD



II 1 GD Ex ia IIC

T90°C

T5...T2

Tamb: -30°C to +70°C

Install Per 420-0004-221-CD

Ui = 30V

Ii = 140mA

Pi = 1w

Ci = 0

Li = 159uH



0344


Test Safe

Ex ia IIC T5 (Ta = -40° C to 70° C) IP66


DIP A21 Ta 100

ANZEx 05.3011X

Wiring



Dimensions



The Point™

Model Numbering (continued on next page)

Technology	
P	RF Admittance
Measurement Type	
N	Std Auto Cal
L	Std 2 pF Fixed
T	10 pF Auto Cal
V	10 pF Fixed
H	Hi Sense .5 pF Auto Cal
P	Hi Sense .5 pF Fixed
G	Hi Sense Manual
M	Std Sense Manual

NOTE: All Calibration modes are built into the standard unit. Modes can be changed in the field as required. (See Instruction Manual)

Input			
T	Two Wire Power Supply 13 to 30 Vdc		
Output			
0	8-16 mA		
Housing			
0	No Approvals, NEMA 4X/IP66, M20 X 1.5 conduit entries		
1	No Approvals, NEMA 4X/IP66, ¾" NPT conduit entries		
2	ATEX / Testsafe Approved, NEMA 4X/IP66, M20 X 1.5 conduit entries		
3	FM / FMc / Testsafe approved, NEMA 4X/IP66, ¾" NPT conduit entries		
5	No Approvals, NEMA 4X/IP66, M20 conduit entries, Dual Seal, Perm-a-Seal sensors – only		
6	No approvals, NEMA 4X/IP66, ¾" NPT conduit entries, Dual Seal, Perm-a-Seal sensors – only		
7	FM / FMc Approved, NEMA 4X/IP66, ¾" NPT conduit entries, Dual Seal, Perm-a-Seal sensors – only		
9	No approvals, NEMA 4X/IP66, M20 conduit entries, Dual Seal, Non Perm-a-Seal sensors – only		
A	No Approvals, NEMA 4X/IP66, ¾" NPT conduit entries, Dual Seal, Non Perm-a-Seal sensors – only		
B	FM / FMc Approved, NEMA 4X/IP66, ¾" NPT conduit entries, Dual Seal, Non Perm-a-Seal sensors – only		
Electronics			
0	Integral		
1	Remote, no cable		
2	Rmt. w/ 3 m (10 ft.) G.P. cable		
3	Rmt. w/ 7.6 m (25 ft.) G.P. cable		
4	Rmt. w/ 10.6 m (35 ft.) G.P. cable		
5	Rmt. w/ 15.2 m (50 ft.) G.P. cable		
6	Rmt. w/ 23 m (75 ft.) G.P. cable		
7	Rmt. w/ (25 ft.) Tri-Ax Cable		
8	Rmt. w/ (50 ft.) Tri-Ax Cable		
9	Rmt. w/ (75 ft.) Tri-Ax Cable		
A	Rmt. w/ (10 ft.) Hi-Temp. Cable		
B	Rmt. w/ (25 ft.) 1st 10ft Hi-Temp. Cbl.		
C	Rmt. w/ (35 ft.) 1st 10ft Hi-Temp. Cbl.		
D	Rmt. w/ (50 ft.) 1st 10ft Hi-Temp. Cbl.		
E	Rmt. w/ (75 ft.) 1st 10ft Hi-Temp. Cbl.		
F	Rmt. w/ (5 ft.) G.P. Cable		
G	Rmt. w/ (5 ft.) Tri-Ax Cable		
H	Rmt. w/ (10 ft.) Tri-Ax Cable		
J	Rmt. w/ (35 ft.) Tri-Ax Cable		
K	Rmt. w/ (5 ft.) Hi-Temp. Cable		
Sensing Element			
Application	Sensing Element	Pressure/Temperature	Wetted Parts
00 General purpose	700-1202-001 remote 700-1202-021 integral	13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and PEEK
01 Floating roof with cable attachment and brass bottom weight	700-1202-012 remote 700-1202-022 integral	13.8 bar @ 177°C (200 PSI @ 350°F)	316SS, Brass, and PEEK
02 General purpose, longer insertion lengths with cable attachment and 316SS bottom weight	700-1202-014 remote 700-1202-024 integral	13.8 bar @ 177°C (200 PSI @ 350°F)	316SS and PEEK
03 Proximity	700-1202-018 remote 700-1202-028 integral	13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and PEEK with 76 mm (3) 316SS proximity plate
04 General purpose, high temperature and pressure	700-1202-041 remote 700-1202-042 integral	69 bar @ 121°C (1000 PSI @ 250°F) 20.7 bar @ 232°C (300 PSI @ 450°F)	316SS and PEEK
06 General purpose with FDA approved materials of construction	700-1202-031 remote 700-1202-032 integral	13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and FDA grade PEEK
07 General purpose Granular materials	700-1202-010 remote 700-1202-020 integral	13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and PEEK with 7/8 inch dia. 316SS collar
09 General purpose Granular materials with FDA approved materials of construction	700-1202-033 remote 700-1202-034 integral	13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and FDA grade PEEK with 7/8 inch dia. 316SS collar
10 Corrosive liquids (2)(4)(9)	700-0001-018 remote	3.4 bar @ 149°C (50 PSI @ 300°F)	PFA
11 General purpose, higher pressure TFE compatibility required	700-0201-005 int/rem	69 bar @ 38°C (1000 PSI @ 100°F) 13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and TFE
12 Corrosive material, higher pressure	700-0201-005 int/rem Hastelloy C	69 bar @ 38°C (1000 PSI @ 100°F) 13.8 bar @ 232°C (200 PSI @ 450°F)	Hastelloy C and TFE
13 Sanitary (3)	700-0201-036 int/rem	69 bar @ 38°C (1000 PSI @ 100°F) 13.8 bar @ 232°C (200 PSI @ 300°F)	316/316L SS and TFE
14 General Purpose, low pressure	700-0202-002 int/rem	3.4 bar @ 149°C (50 PSI @ 300°F) 1.4 bar @ 232°C (20 PSI @ 450°F)	316SS and TFE
15 Heavy duty, agitated tanks or material with high bulk density (1)	700-0202-043 remote	69 bar @ 38°C (1000 PSI @ 100°F) 13.8 bar @ 232°C (200 PSI @ 450°F)	316SS and TFE
16 High Integrity Seal for Hazardous Materials	700-0002-360 int/rem	34.5 bar @ 149°C (500 PSI @ 300°F)	PFA
17 Sanitary (3) lowpressure	700-0202-036 int/rem	3.4 bar @ 149°C (50 PSI @ 300°F)	316SS and TFE
18 Corrosive material, higher pressure with waterlike viscosity (4)	700-0001-022 int/rem	69 bar @ 38°C (1000 PSI @ 100°F) 34.5 bar @ 149°C (500 PSI @ 300°F)	TFE

(Continued on Next Page)

The Point™

Model Numbering (continued from previous page)

	19	Interface Measurement	700-0002-023 int/rem	69 bar @ 38°C (1000 PSI @ 100°F) 34.5 bar @ 149°C (500 PSI @ 300°F)	316SS and TFE
	20	Miniature Pilot Plant Sensor (1)(7)	700-0209-002 remote	6.9 bar @ 121°C (100 PSI @ 250°F) 0 bar @ 232°C (0 PSI @ 450°F)	316 SS and TFE
	Fly Ash Precipitators, Baghouse, and Economizers (1) (6)				
		Application	Sensing Element	Pressure/Temperature	Wetted Parts
	31	No hopper Installation	700-0029-001 remote	0.1 bar @ 260°C (2 PSI @ 500°F)	316SS and TFE
	32	Hopper Installation up to 200mm (8 inches)	700-0029-002 remote	0.1 bar @ 260°C (2 PSI @ 500°F)	316SS and TFE
	33	Hopper Installation up to 406mm (16 inches)	700-0029-003 remote	0.1 bar @ 260°C (2 PSI @ 500°F)	316SS and TFE
	34	Hopper Installation up to 521mm (20.5 inches)	700-0029-004 remote	0.1 bar @ 260°C (2 PSI @ 500°F)	316SS and TFE
	35	Hopper Installation up to 635mm (25 inches)	700-0029-005 remote	0.1 bar @ 260°C (2 PSI @ 500°F)	316SS and TFE
	Plugged Chute Detection (1) (5)				
		Application	Sensing Element	Pressure/Temperature	Wetted Parts
	50	Flush Mount Sensor 305mm ² (12 inches ²) heavy duty	700-0207-001 remote	0.1 bar @ 82°C (1 PSI @ 180°F)	304 SS and Polyurethane
	51	Flush Mount Sensor 305mm ² (12 inches ²) higher temperature	700-0207-002 remote	0.1 bar @ 149°C (1 PSI @ 300°F)	304 SS and TFE
	52	Flush Mount Sensor 305mm ² (12 inches ²) with curved radius 153, 229, 305 mm (6, 9, or 12 inches)	700-0207-003 remote	0.1 bar @ 82°C (1 PSI @ 180°F)	304 SS and Neoprene
	53	Flush Mount Sensor 305mm ² (12 inches ²) extra heavy duty	700-0207-004 remote	0.1 bar @ 82°C (1 PSI @ 180°F)	410 SS and UHMW Polyethylene
	55	Flush Mount Sensor 203mm ² (8 inches ²) heavy duty	700-0207-006 remote	0.1 bar @ 82°C (1 PSI @ 180°F)	304 SS and Polyurethane
	High Pressure / High Temperature				
	60	High Pressure & Temp.	700-0204-038 remote	137.9 bar @ 93°C (2000 PSI @ 200°F) 68.9 bar @ 260°C (1000 PSI @ 500°F)	316SS and Ceramic
	61	High Temperature	700-0204-002 remote	0 bar @ 816°C (0 PSI @ 1500°F)	316SS and Ceramic
	62	High Pressure & Temp.	700-0204-048 remote	275.8 bar @ 316°C (4000 PSI @ 600°F)	316SS
	ZZ	Sensing Element Not Listed			
	Mounting Type (See separate Mounting Chart for first three digits)				
		IL	CSL	IL	CSL
	xxx1	457 mm (18")	152 mm (6")	xxxG	457 mm (18") 0 mm (0")
	xxx2	305 mm (12")	152 mm (6")	xxxH	914 mm (36") 254 mm (10")
	xxxA	152 mm (6")	51 mm (2")	xxxJ	914 mm (36") 0 mm (0")
	xxxB	305 mm (12")	51 mm (2")	xxxK	1219 mm (48") 254 mm (10")
	xxxC	305 mm (12")	89 mm (3.5")	xxxL	1524 mm (60") 254 mm (10")
	xxxD	457 mm (18")	51 mm (2")	P00X	IL/CSL Other
	xxxE	457 mm (18")	89 mm (3.5")	A1BX	IL/CSL factory set for Fly Ash
	xxxF	457 mm (18")	254 mm (10")	xxxZ	Other



Not all mounting options available with all sensing elements

- Notes:** CSL (Cote-Shield Length) should extend through Nozzle + Typical "Wall Buildup" + 2 Inches
- (1) Available with remote electronics only
 - (2) Use A1P mounting option
 - (3) Choose only sanitary mounting options
 - (4) Available with 0-inch CSL only
 - (5) Use P00X mounting option
 - (6) Use A1B mounting option
 - (7) Use A8B mounting option (1/4-inch NPT)
 - (8) Choose from flange mounting only
 - (9) FM approved with remote electronics only

NPT Threads			
A1B	3/4"NPT	316SS	A2B 1"NPT 316SS
A1C	3/4"NPT	Hastelloy C	A2C 1"NPT Hastelloy C
A1P	3/4"NPT	PFA	

Sanitary TriClamps			
C2B	1"TriClamp	316SS	C4B 2"TriClamp 316SS
C3B	1 1/2"TriClamp	316SS	

DIN Flanges			
E01	25 mm	16 bar	RF 316/316L SS
EP1	25 mm	40 bar	RF 316/316L SS
EQ1	50 mm	16 bar	RF 316/316L SS
ER1	50 mm	40 bar	RF 316/316L SS
ES1	80 mm	16 bar	RF 316/316L SS
ET1	80 mm	40 bar	RF 316/316L SS
EU1	100 mm	16 bar	RF 316/316L SS
EV1	100 mm	40 bar	RF 316/316L SS
EW1	150 mm	16 bar	RF 316/316L SS
EX1	150 mm	40 bar	RF 316/316L SS
E02	25 mm	16 bar	RF CS
EP2	25 mm	40 bar	RF CS
EQ2	50 mm	16 bar	RF CS
ER2	50 mm	40 bar	RF CS
ES2	80 mm	16 bar	RF CS
ET2	80 mm	40 bar	RF CS
EU2	100 mm	16 bar	RF CS
EV2	100 mm	40 bar	RF CS
EW2	150 mm	16 bar	RF CS
EX2	150 mm	40 bar	RF CS

ANSI Flanges			
DA1	1"	150#	RF 316/316L SS
DB1	1 1/2"	150#	RF 316/316L SS
DC1	2"	150#	RF 316/316L SS
DD1	2 1/2"	150#	RF 316/316L SS
DE1	1"	300#	RF 316/316L SS
DF1	1 1/2"	300#	RF 316/316L SS
DG1	2"	300#	RF 316/316L SS
DH1	2 1/2"	300#	RF 316/316L SS
DI1	3"	150#	RF 316/316L SS
DJ1	3"	300#	RF 316/316L SS
DK1	4"	150#	RF 316/316L SS
DL1	4"	300#	RF 316/316L SS
DM1	6"	150#	RF 316/316L SS
DN1	6"	300#	RF 316/316L SS
DA2	1"	150#	RF CS
DB2	1 1/2"	150#	RF CS
DC2	2"	150#	RF CS
DD2	2 1/2"	150#	RF CS
DE2	1"	300#	RF CS
DF2	1 1/2"	300#	RF CS
DG2	2"	300#	RF CS
DH2	2 1/2"	300#	RF CS
DI2	3"	150#	RF CS
DJ2	3"	300#	RF CS
DK2	4"	150#	RF CS
DL2	4"	300#	RF CS
DM2	6"	150#	RF CS
DN2	6"	300#	RF CS